



## CSL 630 TIC

IN-CEILING SPEAKERS

### In-ceiling speaker with metal grille



- Metal back cover
- Colour white RAL9016,
- Coaxial loudspeaker with 6" woofer and 1/2" tweeter
- Nominal Power 3.8/7.5/15/30W/80hm with 100V/70V line transformer
- 90-20,000Hz frequency response
- 88dB+/- 3dB sensitivity @1W/1m
- Dimensions 230x150mm
- Building-in hole 200mm



## CSL 840 TIC

### In-ceiling speaker with metal grille

- Metal back cover
- Colour white RAL9016,
- Coaxial loudspeaker with 8" woofer and 1/2" tweeter
- Nominal Power 5/10/20/40W/80hm with 100V/70V line transformer
- 90-20,000Hz frequency response
- 88dB+/- 3dB sensitivity @1W/1m
- Dimension 270x185mm
- Building-in hole 240mm




	CSL 630 TIC	CSL 840 TIC
<b>Code</b>	<b>29417</b>	<b>29418</b>
<b>Power taps</b>	3.8/7.5/15/30W/80hm	5/10/20/40W/80hm
<b>Frequency response</b>	90:20.000Hz	50:20.000Hz
<b>Sensitivity 1W/1m</b>	88dB	88dB
<b>Input voltage</b>	100V / 70V	100V / 70V
<b>Cut-out diameter</b>	200mm	240mm
<b>Weight</b>	2,3 Kg	3,1 Kg
<b>Dimensions</b>	ø 230x150mm	ø 270x185mm

## CSL 606 TWP

WEATHER-PROOF SPEAKERS

### ABS weather-proof in-ceiling speaker

- Plastic basket and white RAL 9016 grille
- 5" loudspeaker with coaxial 1" tweeter, water-resistant and resistant to the corrosion due to outdoor mounting
- 100V integrated transformer
- Low impedance socket (8ohm)
- Maximum power 45W (Rated 20W)



	CSL 606 TWP
<b>Code</b>	<b>29429</b>
<b>Power taps</b>	20W/80hm
<b>Frequency response</b>	95:20.000Hz
<b>Sensitivity 1W/1m</b>	90dB
<b>Input</b>	100V / 80hm
<b>Cut-out diameter</b>	122mm
<b>Weight</b>	0,7 Kg
<b>Dimensions</b>	ø 167x115mm