


## Installation Instructions



### Smart 0-10V Dimmer

Product Code:  
**KASTA-D1-10VIB**

#### APP Installation

Visit [www.kasta.com.au](http://www.kasta.com.au) or your app store to download the free KASTA app.  
iOS: requires iOS 9.0 or later.  
Android: requires Android 4.4 or later.  
Devices must support Bluetooth 4.0



#### Important Safety Information

- This product must be installed by a licensed electrician in accordance with all the requirements of AS/NZS 3000 (current edition) and other relevant Standards and Regulations.
- Electricity MUST be disconnected prior to installation. Failure to do so may result in serious injury and or loss of life.
- Indoor use only. Not suitable for damp or explosive environments
- Complies to Australian Standards AS/NZS 60669.2.1:2013 with AS/NZS 60669.1:2013 (IEC 60669-2-1 Ed. 4.1 MOD with IEC 60669-1 Ed.3.2 MOD).
- No user serviceable parts inside.

#### FEATURES

- Smart functions via phone/tablet with the app such as schedules, timers, scenes and groups.
- Dimmable (via KASTA app, KASTA remotes, KASTA SLO2AB-BH or Push button momentary switch only).
- To prevent a reduction in Bluetooth signal strength, install with line of sight between devices if possible.
- 0-10V output signal suitable for 0-10V LED driver.
- Controls the output according to the Bluetooth® signal received from the daylight sensor.

#### FUNCTION SETUP

(using smart remote switch or momentary switch)

ON/OFF SWITCH	SHORT PRESS
Turns lights on or off.	
DIM UP/DOWN	ONE LONG PRESS
When lights are on, long press button to dim up or down. Release button to stop.	
FULL BRIGHTNESS	2 CLICKS
Sets lights to full brightness.	
ADD DELAY TO OFF	3 CLICKS*
Lights automatically turns off after set time.	
RESTORE TO FACTORY SETTINGS	9 CLICKS

Reset password to the default setting.

\*If successful, light will pulse the number of times that the switch was clicked, indicating function.

#### TECHNICAL SPECIFICATIONS

**Supply:** 220-240V~50/60Hz

**Operating Frequency:** 2.4Ghz

**Output Current (Max.):** 40mA

**Operating Temp:** -20°C to 50°C

**Dimming Method:** 1-10V

**IP Rating:** IP20

**Maximum Number of Drivers:** 30

**Dimensions:** 45x45x25mm

#### CONNECTION DIAGRAM

