

NEW FOR



# 19" Racking Systems

Constructed from 1.5mm black powdercoated steel, these freestanding 19" racks are ideal for communications, public address and IT server rooms. Each package includes a rack frame, tempered glass front door, steel rear door and two side panels and top. Each door & panel is lockable. Front door can be rotated to open from left to right, or right to left. Design includes plenty of ventilation to keep equipment cool. Supplied flatpack and assembles quickly.

## Features

- IP20 rated protection.
- RAL9004/5 black colour.
- SPCC cold rolled steel construction with 1.5mm steel mounting posts and back panel, 1.2mm frame.
- Designed to comply with 19" international standard.
- Complies with ANSI/EIA RS-310-D, IEC297- 2, DIN41491 - PART1, DIN41494 - PART7, GB/3047.2-92 standard.
- Adjustable mounting post to suit different depth equipment.
- Tempered glass front door with 180 deg. rotatable lock.
- Removable side and rear panels for easy installation and adjustment of equipment.
- Ventilation in all doors.
- Cable entry on the top cover.
- Adjustable cable entries in the bottom with panels.
- Adjustable feet and universal castors included.
- Cooling fan holes in top cover.
- Supplied flat pack - assembles quickly.

## Pricing

600mm Depth	Dimensions
HD5416 16RU	600W x 600D x 875H mm
HD5420 20RU	600W x 600D x 1062H mm
HD5425 25RU	600W x 600D x 1285H mm
HD5430 30RU	600W x 600D x 1507H mm
HD5435 35RU	600W x 600D x 1729H mm
HD5442 42RU	600W x 600D x 2040H mm
800mm Depth	
HD5542 42RU	600W x 800D x 2040H mm

## Each system includes:

- Front and rear doors
- Side panels
- Equipment shelf
- Wheels, feet, screws and cage nuts.
- Cable management panel
- 2U blanking panels
- Two cooling fans



Each includes lockable rear door.