



Shown with door removed.

## 19" Racking Systems Wall Mount/Freestanding

Constructed from 1.5mm black powdercoated steel, these 19" racks are ideal for communications, public address and IT server rooms. The design offers both the option of wall mounting or floor standing as desired. Each package includes a rack frame, tempered glass front door, removeable rear and side panels, top and bottom panels. The front door and side panels are lockable. Front door can be rotated to open from left to right, or right to left. Provision for cooling fans in top. Design includes plenty of ventilation to keep equipment cool. For floorstanding installations H 5296 optional caster set may be fitted for added mobility. Supplied flatpack and assembles quickly.

## **Features**

- IP20 rated protection.
- RAL9004/5 black colour.
- SPCC cold rolled steel construction with 1.5mm steel mounting posts and back panel, 1.2mm frame.
- Designed to comply with 19" international standard.
- Complies with ANSI/EIA RS-310-D, IEC297-2, DIN41491 PART1, DIN41494 PART7, GB/3047.2-92 standard.
- Adjustable mounting post to suit different depth equipment.
- Tempered glass front door with 180 deg. rotatable lock.
- Removable side and rear panels for easy installation and adjustment of equipment.
- Ventilation in all doors.
- Cable entry on the top cover.
- Adjustable cable entries in the bottom with panels.
- · Adjustable feet included.
- Includes screws and cage nuts.
- Cooling fan holes in top cover.
- Supplied flat pack assembles guickly.

## Pricing

450mm Depth	Dimensions
HD5506 6RU	530W x 450D x 360H mm
HD5509 9RU	530W x 450D x 493H mm
HD5512 12RU	530W x 450D x 626H mm
HD5515 15RU	530W x 450D x 760H mm
HD5518 18RU	530W x 450D x 894H mm
HD5522 22RU	530W x 450D x 1071H mm
Extras	
H 5296	Caster wheel kit Pk4

## Ideal for:

- DVR and security equipment
- Background music PA systems
- UPS power backup equipment
- Patch panels and switches
- Telephone systems and PABX
- Network and comms gear