

INSTRUCTION MANUAL

C 0891/C 0893

Quick-Mount Wall Speakers

WARNING !

- Installation by qualified persons only.
- Do not select another adjustment if the speaker is in use !
- No naked flame sources, such as lighted candles, should be placed on the apparatus.
- Minimum distances of 30mm around the apparatus for sufficient ventilation.
- Do not use appliance in tropical and/or temperate climate.
- Not to be exposed dripping or splashing.

SPECIFICATION :

Model No.	C 0891	C 0893
Rated Power (rms)	6W	
Impedance	1667Ω, 3333Ω, 6667Ω, 13333Ω	
Power Taps @ 100V	6W, 3W, 1.5W & 0.75W	
Power Taps @ 70.7V	3W, 1.5W, 0.75W & 0.375W	
SPL (1W/1M)	95dB	
Max. SPL (6W/1M)	102dB	
Freq. Range (-10dB)	160 Hz ~ 20K Hz	
Dispersion 1K Hz/4K Hz	120° / 80°	
Dimension (W × H × D)	210 (8.27) × 210 (8.27) × 85 (3.35) mm. (in.)	
Material	UL94V0 ABS Cabinet and Aluminium backplate.	
Colour/Finish	White (RAL 9016)	
Power Selection Way	Plug	
Volume Control	n.a.	Available
Weight	1.3 Kgs (2.87 lbs.)	
Mounting	Screws and Key-hole	

Frequency Response

